

# ACUROS<sup>®</sup> CQD<sup>®</sup> SWIR and eSWIR Cameras

## BRD8226/D

ACUROS CQD SWIR and eSWIR cameras are designed for high-resolution, broadband imaging and come equipped with single-stage TECs for lower noise operation and greater image stability. Brilliant, high-resolution images are delivered with high frame rates, high dynamic range, and a broad range of exposure times. Our pioneering sensor technology enables the first commercially available 5.9 megapixel CQD SWIR and eSWIR products of their kind. Our 400–2100 nm eSWIR and 400–1700 nm SWIR responsivity sensors deliver the broadest bandwidths for maximum utility, and our CQD sensor processing enables lower costs per megapixel. ACUROS cameras are GenICam<sup>™</sup> compliant and come equipped with USB3 or GigE Vision or Camera Link interfaces. The cameras are designated EAR-99, requiring no license for lawful export.

### Sensor Technology

CQD sensors are fabricated via deposition of quantum dot semiconductor crystals directly upon the surface of the silicon wafer. The resulting CQD photodiode array enables higher resolution, smaller pixel pitch, broader bandwidth, low noise, and low inter-pixel crosstalk, eliminating the prohibitively expensive hybridization process inherent to InGaAs sensors. CQD sensor technology is silicon wafer-scale compatible, opening it's potential to very low-cost high-volume applications.




Figure 2. ACUROS CQD Sensor



Figure 1. ACUROS CQD SWIR Cameras

### Features

- Resolutions up to 5.9 MP Available
- TEC Cooling for Low Noise
- Full Visible-to-eSWIR
- USB3 Vision<sup>®</sup>, GigE Vision<sup>®</sup> and Camera Link Interfaces
- C-, M42 Mount Interfaces
- Compatible with Most SWIR Lenses
- Software GUI for Camera Control
- Pixel Non-uniformity Correction
- SDK Available for User Development

### Applications

- Machine Vision
- Silicon Inspection
- Instrumentation
- Beam Profiling
- Battery Inspection
- Surveillance
- Hyperspectral
- Chemical Sensing
- Agriculture
- Medical Imaging

# BRD8226/D

## ACUROS PRODUCT TABLE

Part Numbers	Resolution	Megapixel	Interface	Frame Rate (FPS)	Pixel Pitch (μm)	Spectral Sensitivity (nm)	Lens Mounts
--------------	------------	-----------	-----------	------------------	------------------	---------------------------	-------------

### Standard SWIR

ACUROS-0640-GIGE-001	640 x 512	0.33	GigE	270 fps	15 x 15	400–1700	C, M-42
ACUROS-0640-USB3-001	640 x 512	0.33	USB3	270 fps	15 x 15	400–1700	C, M-42
ACUROS-1280-GIGE-001	1280 x 1024	1.31	GigE	88 fps	15 x 15	400–1700	C, M-42
ACUROS-1280-USB3-001	1280 x 1024	1.31	USB3	88 fps	15 x 15	400–1700	C, M-42
ACUROS-1920-GIGE-001	1920 x 1080	2.07	GigE	58 fps	15 x 15	400–1700	M-42
ACUROS-1920-USB3-001	1920 x 1080	2.07	USB3	58 fps	15 x 15	400–1700	M-42
ACUROS4-SWIR-CLINK	2040 x 2040	4.2	Camera Link	100 fps	7 x 7	400–1700	M-42
ACUROS6-SWIR-CLINK	2908 x 2040	5.3	Camera Link	100 fps	7 x 7	400–1700	M-42

### eSWIR

ACUROS-0640-GIGE-002	640 x 512	0.33	GigE	270 fps	15 x 15	400–2100	C, M-42
ACUROS-0640-USB3-002	640 x 512	0.33	USB3	270 fps	15 x 15	400–2100	C, M-42
ACUROS-1280-GIGE-002	1280 x 1024	1.31	GigE	88 fps	15 x 15	400–2100	C, M-42
ACUROS-1280-USB3-002	1280 x 1024	1.31	USB3	88 fps	15 x 15	400–2100	C, M-42
ACUROS-1920-GIGE-002	1920 x 1080	2.07	GigE	58 fps	15 x 15	400–2100	M-42
ACUROS-1920-USB3-002	1920 x 1080	2.07	USB3	58 fps	15 x 15	400–2100	M-42
ACUROS4-ESWIR-CLINK	2040 x 2040	4.2	Camera Link	100 fps	7 x 7	400–2100	M-42
ACUROS6-ESWIR-CLINK	2908 x 2040	5.9	Camera Link	100 fps	7 x 7	400–2100	M-42

### LASER BEAM PROFILING STANDARD SWIR

ACUROS-0640-GIGE-003	640 x 512	0.33	GigE	270 fps	15 x 15	400–1700	None needed for Laser Profiling cameras
ACUROS-0640-USB3-003	640 x 512	0.33	USB3	270 fps	15 x 15	400–1700	
ACUROS-1280-GIGE-003	1280 x 1024	1.31	GigE	88 fps	15 x 15	400–1700	
ACUROS-1280-USB3-003	1280 x 1024	1.31	USB3	88 fps	15 x 15	400–1700	
ACUROS-1920-GIGE-003	1920 x 1080	2.07	GigE	58 fps	15 x 15	400–1700	
ACUROS-1920-USB3-003	1920 x 1080	2.07	USB3	58 fps	15 x 15	400–1700	
ACUROS4-SWIR-CLINK-LBP	2040 x 2040	4.2	Camera Link	100 fps	7 x 7	400–1700	
ACUROS6-SWIR-CLINK-LBP	2908 x 2040	5.9	Camera Link	100 fps	7 x 7	400–1700	

### LASER BEAM PROFILING eSWIR

ACUROS-0640-GIGE-004	640 x 512	0.33	GigE	270 fps	15 x 15	400–2100	None needed for Laser Profiling cameras
ACUROS-0640-USB3-004	640 x 512	0.33	USB3	270 fps	15 x 15	400–2100	
ACUROS-1280-GIGE-004	1280 x 1024	1.31	GigE	88 fps	15 x 15	400–2100	
ACUROS-1280-USB3-004	1280 x 1024	1.31	USB3	88 fps	15 x 15	400–2100	
ACUROS-1920-GIGE-004	1920 x 1080	2.07	GigE	58 fps	15 x 15	400–2100	
ACUROS-1920-USB3-004	1920 x 1080	2.07	USB3	58 fps	15 x 15	400–2100	
ACUROS4-ESWIR-CLINK-LBP	2040 x 2040	4.2	Camera Link	100 fps	7 x 7	400–2100	
ACUROS6-ESWIR-CLINK-LBP	2908 x 2040	5.9	Camera Link	100 fps	7 x 7	400–2100	

\*All Part Number's listed feature Global Shutters and TEC Cooling

ACUROS and CQD are registered trademarks of Semiconductor Components Industries, LLC dba "onsemi" or its affiliates and/or subsidiaries in the United States and/or other countries.

All other brand names and product names appearing in this document are registered trademarks or trademarks of their respective holders.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marketing.pdf](http://www.onsemi.com/site/pdf/Patent-Marketing.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS:**

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

**ONLINE SUPPORT:** [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)